

CAT. 6A Keystone Coupler, STP

Part no.: NK4017

Technical Features


CAT.6A 10G 500MHz class EA

2 x RJ45 jack, fully shielded

Slim type

Zinc alloy housing

Technical Drawings



Unit: mm

Environmental:

1. Storage: $-40^{\circ} \sim 70^{\circ}$
2. Operation: $-10^{\circ} \sim 60^{\circ}$

Mechanical:

1. RJ45 Contact Life: 750 times min.
2. Plug Inforce: $< 30N$

Electrical:

1. Contact Resistance: $20M\Omega$ max.
2. Insulation Resistance: $500M\Omega$ min. @500V DC
3. Withstand Voltage: DC 1000V AC 700V RMS 60Hz, 1MIN
4. Component Testing for Cat.6A to ISO/IEC 11801 Ed.2.2: 2011-06
DIN EN 50173-1:2011-09
TIA/EIA-568-C.2 (2009-08)

NK4017



4 0527 920 5751 5

Made in China

www.logilink.com



RoHS
compliant

*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.

Package Contents

Cat.6A Keystone Coupler x 1

Packaging Information

Packing Dimension	mm
Packing Weight	kg
Carton Dimension	mm
Carton Q'ty	pcs
Carton Weight	kg



NK4017



4 0527 920 5751 5

Made in China

www.logilink.com



RoHS
compliant

*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.